TRAIL ASSESSMENT FORM

Doc. #	3005	Trail N	Name	Sassaman Notch Path	Trail Type:	M	Condition	Fair	
D4			E		1	I=(
Route:			From mk 3135 to Chickatawbut Rd, 967 yds(.55 mi)						
Recent Weather:			1" snow covering some portions of trail, some icy spots, no precip past 7						
TDAII			days Start at mk 3135 int with Wompatuck Path.						
TRAIL		70	Trail starts steeply up fall line. Some recent rkw evident in an attempt to						
LAND	MAKK	72	slow water flow(1)						
			20 yd rk wb fc						
			34.3 yd rk wb fc						
			At this wb the trail turns left up along contour						
			35.9 yd rk wb fc						
			36 yd rk wb fc						
			80 yds du right						
			93 yd runoff stream crossing steady flow R to L 3" deep x 1.5 ft (2)						
				d step-type rk wb nf					
				d rk wb fc					
			-	d rk wb fc					
			-	d rk wb fc trail turns le	eft				
			-	d sbd(3)	(D E (.1			
			518 yd mk3103 int with Great Dome Foot path						
			Trail bears left after int with Skyline Trail 613 mk 3090 not on maps (Int of Red dot and Vellow Dot loops with Slide						
			613 mk3090 not on maps (Int of Red dot and Yellow Dot loops with Slide Notch Trail/Path)						
				begins steep descent to	flat area hn				
				d sbd(4)	riat area bii				
			704 yd runoff stream following trail in dt on left, settling onto and across						
			trail(6		8	,	8		
			,	d sbd (5)					
			_	d nameless trail on left	no mk				
			795 y	d nameless trail on left	no mk				
			812	yd sbd(7)					
			-	d mk3075 trail on righ	t to pavilion, or	ı left, smal	l social trail		
			-	d sbd (8)					
				d sbd(9)					
		Trail starts downhill descent down the fall-line. There have been some apparent attempts to divert water flow off the trail with shovel knicks but no							
				_	vater flow off th	ne tran wit	n snovei knic	eks but no	
				rd(10)	what Bood Gro	nita nast w	ith Cassaman	Notah	
			967 yd fire gate at Chickatawbut Road Granite post with Sassaman Notch Path. 'No bicycles' badge on tree.						
			ı auı.	140 dicycles dauge of	i ucc.				
MINOI	2		(3)tra	il saw and crew of 3					
PROBLEM			(4)trail saw and crew of 3						
			(6) rd and knick recommended						
AREAS		(7) trail saw and crew of 3							
			(8) tra	ail saw and crew of 3					
			(9) tra	ail saw and crew of 3					
				ushing needed except v					
MAJO	<u>R</u>		(1) these 'steps' approx	every 10 yd are	nf. Need t	to correct by	angling	

PROBLEM AREAS	and providing drainage. (2) Recommend armoring the water crossing to ensure no trail dg (10) need to design and install rd, wb where needed to prevent any more					
	trail erosion					
DISTANCES TO	523 yd to Skyline Trail.					
MAJOR	967 yd from beginning at Wompatuck Path to end at Chickatawbut Road					
INTERSECTIONS						
Report prepared by:	Steve Cobble	Assessment date:	01/23/08			

Abbreviations:

Usage type: foot traffic only (H), multi-use (M)

waterbars (wb) small blowdowns (sbd) culverts(cv) large blowdowns (lbd)

rolling dips (rd) rock work (rkw)

bridges (br) bridge building (bbd), ditches (dt)

excessive erosion (ee) leaning tree (lt)) intersection marker(mk) dugout(du)

bog bridges (bb) culvert replacement (cr)

non-functioning(nf) functioning(fc)

damage(dg) corrugated plastic(cp)

not needed(nn)

rock stairs (rs) trail relocation (tr),

cribbing (cb) building new trail drainage (ntd)

retaining walls (rw) brushing needed (bn)

clay(cl)